Formerly RFF-SC, 1st Ed., 1970

11303

ARROYO COLORADO EXTENSION
SCALE 1:40,000
Nautical Miles
Statute Miles
Yards
LATITUDE
LONGITUDE

CHANNEL TO PORT HARLINGEN

TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - REPORT OF AUG 2015

CONTROLLING DEPTHS FROM SEWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)				PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE HALF OF QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE HALF OF QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (MILES)	DEPTH MLLW (FEET)
NORTH WYE	11.6	11.8	9.8	5-15	—	—	12
SOUTH WYE	9.5	11.0	11.0	5-15	—	—	12
MILE 0 TO MILE 8 (STATUTE)	10.0	13.5	11.6	5-15	200-125	8.0	12
MILE 0 TO MILE 20	9.6	12.0	9.1	5-15	125	12.0	12
MILE 20 TO MILE 24.4	11.2	12.6	10.2	5-15	125	3.9	12
TURNING BASIN	13.8	14.0	13.5	5-15	400	0.1	12

NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

PLANE COORDINATE GRID
(based on NAD 1927)
The Texas State Grid is indicated on this chart at 10,000 foot intervals thus: The last three digits are omitted.

CAUTION
SUBMARINE PIPELINES AND CABLES
Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Pipeline Area — Cable Area

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.
Covered wells may be marked by lighted or unlighted buoys

WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

CAUTION
GAS AND OIL WELL STRUCTURES
Uncharted platforms, gas and oil well structures, pipes, piles and stakes can exist within the limits of this chart.

NOAA WEATHER RADIO BROADCASTS
The NOAA Weather Radio station listed below provides continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Brownsville, TX	WWG-34	162.550 MHz

CAUTION
Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.
Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.
Station positions are shown thus:
⊙(Accurate location) ⊕(Approximate location)

AUTHORITIES
Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

CAUTION
Stakes, piles and platforms, some submerged, may exist between charted piling and platforms along the maintained channels.
Piles and platforms are not shown where they interfere with a light symbol.

HORIZONTAL DATUM
The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 1.256" northward and 0.933" westward to agree with this chart.

FISHING AND HUNTING STRUCTURES
Uncharted fish and wildlife harvesting devices and structures such as fish traps, pound nets, crab traps, and duck blinds, some submerged, may exist in the area of this chart, particularly in the near shore area. Mariners should proceed with caution.

AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

ACKNOWLEDGMENT
The National Ocean Service acknowledges the exceptional cooperation received from members of the Lower Rio Grande Valley Power Squadron, District 21, United States Power Squadrons, in continually providing essential information for revising this chart.

TIDAL INFORMATION
In Laguna Madre and adjacent bays the periodic tide has a mean range of less than one half foot, except near the Gulf inlet. Water stages vary greatly with weather conditions.
Areas that are frequently submerged are shown by a green tint.
The broken shoreline symbol represents an approximate mean high water line.

HURRICANES AND TROPICAL STORMS
Hurricanes, tropical storms and other major storms may cause considerable damage to marine structures, aids to navigation and moored vessels, resulting in submerged debris and shoaling.
Charted soundings, channel depths and shoreline may not reflect actual conditions following these storms. Fixed aids to navigation may have been damaged or destroyed. Buoys may have been moved from their charted positions, damaged, sunk, extinguished or otherwise made inoperative. Mariners should not rely upon the position or operation of an aid to navigation. Wrecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.
Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard unit.

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

JOINS ARROYO COLORADO EXTENSION

INTRACOASTAL WATERWAY AIDS
The U.S. Aids to Navigation System is designed for use with nautical charts, and the exact meaning of an aid to navigation may not be clear unless the appropriate chart is consulted.
Aids to navigation marking the Intracoastal Waterway exhibit unique yellow symbols to distinguish them from aids marking other waterways.
When following the Intracoastal Waterway westward from Carrabelle, FL to Brownsville, TX, aids with yellow triangles should be kept on the starboard side of the vessel and aids with yellow squares should be kept on the port side of the vessel.
A horizontal yellow band provides no lateral information, but simply identifies aids for navigation as marking the Intracoastal Waterway.

INTRACOASTAL WATERWAY
Project Depths
12 feet Carrabelle, FL to Brownsville, TX.
The controlling depths are published periodically in the U.S. Coast Guard Local Notice to Mariners.

Distances
Mileage distances shown along the Waterway are from Harvey Locks, Louisiana to Harvey Lock, LA, and are indicated thus: ——
Mileage distances shown along Arroyo Colorado Cutoff are in Statute Miles, based on zero at its intersection with the Intracoastal Waterway and are indicated thus: ——
Tables for converting Statute Miles to International Nautical Miles are given in U.S. Coast Pilot 5.

THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES

TEXAS - INTRACOASTAL WATERWAY

LAGUNA MADRE

CHUBBY ISLAND TO STOVER POINT INCLUDING THE ARROYO COLORADO

Mercator Projection
Scale 1:40,000 at Lat 26° 20'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

For Symbols and Abbreviations see Chart No. 1

Additional information can be obtained at nauticalcharts.noaa.gov.

HEIGHTS
Heights in meters above Mean High Water.

SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 5 for important supplemental information.

CAUTION
Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

CAUTION
Many uncharted rocks exist in Laguna Madre.

CONTINUED ON CHART 11301

22nd Ed., Jan. 2014
11303
Last Correction: 4/26/2016. Cleared through:
LNM: 4016 (10/4/2016), NM: 4316 (10/22/2016)

CAUTION
This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

To ensure that this chart was printed at the proper scale, the line below should measure six inches (152 millimeters). If the line does not measure six inches (152 millimeters), this copy is not certified safe for navigation.

NOAA encourages users to submit inquiries, discrepancies or comments about this chart at http://www.nauticalcharts.noaa.gov/staff/contact.htm

SOUNDING IN FEET

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

This chart was distributed as a PDF (Portable Document Format). Printing PDFs may alter the chart scale, color, or legibility that may impact suitability for navigation. Printed charts provided by NOAA certified Print on Demand (POD) providers fulfill a vessel's requirement to carry a navigational chart "published by the National Ocean Service" in accordance with federal regulations, including but not limited to 33 C.F.R. 164.33(a), 33 C.F.R. 164.72(b), and 46 C.F.R. 28.225(a). POD charts meet stringent print standards and can be recognized by an official certification of authenticity printed on the chart. A list of POD providers can be found at: nauticalcharts.noaa.gov/pod

Laguna Madre
Chubby Island To Stover Point
SOUNDINGS IN FEET - SCALE 1:40,000

11303