Formerly CAGS 1116, 1a Ed., Jan 1918; C-1050-183 KAPP 49

THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES - GULF COAST

MISSISSIPPI RIVER TO GALVESTON

Mercator Projection
Scale 1:458,596 at Lat 28° 52'
North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FATHOMS
AT MEAN LOWER LOW WATER

Additional information can be obtained at nauticalcharts.noaa.gov

(For offshore navigation only)
Floating Aids to Navigation inside the sea Buoys are not shown on this chart.
See 1:80,000 series and large scale harbor charts for aids marking maintained channels.

NOTE H
The U.S. Coast Guard operates a mandatory Vessel Traffic Services (VTS) system in the Houston, Galveston, and Texas City waterways. Vessel operating procedures and designated radiotelephone frequencies are published in 33 CFR 161; the U.S. Coast Pilot; and the VTS User's Manual. Mariners should consult these sources for applicable rules and reporting requirements. "Houston Traffic" is a full service VTS, providing a continuous Information Service, Traffic Organization Services as requisite, and Navigation Assistance Service upon request.

NOTE B
GALVESTON TRAFFIC SEPARATION SCHEME
A pilot boarding area is located near the center of the inshore precautionary area. Due to heavy vessel traffic, mariners are advised not to anchor or linger in this precautionary area except to pick up or disembark a pilot.

NOTE F
The U.S. Coast Guard operates a mandatory Vessel Traffic Services (VTS) on the Sabine - Neches Waterway and offshore approaches. Vessel operating procedures, mandatory participation boundaries, and designated radiotelephone frequencies are published in 33 CFR 161; the U.S. Coast Pilot; and the VTS Port Arthur User Manual. Mariners should consult these sources for applicable rules and reporting requirements. "Port Arthur Traffic" is a full service VTS, providing a continuous Information Service, Traffic Organization Services and Navigational Assistance Services as required.

CAUTION
Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117, Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.
Station positions are shown thus:
(C)(Accurate location) o(Approximate location)

HURRICANES AND TROPICAL STORMS
Hurricanes, tropical storms and other major storms may cause extensive damage to navigation aids, alter navigation and injured vessels, resulting in submerged debris in unknown locations.
Charted soundings, channel depths and shoreline may not reflect actual conditions following these storms. Fixed aids to navigation may have been damaged or destroyed. Buoys may have been moved from their charted positions, damaged, destroyed, or replaced with temporary markers. Mariners should not rely upon the position or operation of an aid to navigation. Wrecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.
Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard unit.

ARTICULATED AIDS
An articulated aid to navigation consists of a physical aid to navigation and a submerged mooring coupling connected to a sinker. The structure is kept upright by the buoyancy of a submerged flotation chamber. It is designed primarily to mark narrow channels in depths of up to 60 feet. All articulated aids are labelled "AR".

For Symbols and Abbreviations see Chart No. 1

HEIGHTS
Heights in feet above Mean High Water.

AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

AUTHORITIES
Hydrography and topography by the National Ocean Service, Coast Survey with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 5. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations governing the waters of the United States may be obtained from the Eighth Coast Guard District in New Orleans, La., or at the Office of the District Engineer, Corps of Engineers in Galveston, TX and New Orleans, LA.
Refer to charted regulation section numbers.

CAUTION
SUBMARINE PIPELINES AND CABLES
Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:
Pipeline Area — Cable Area
Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried; those that were originally buried may have become exposed. Mariners should exercise caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.
Covered wells may be marked by lighted or unlighted buoys.

NOTE E
The Gulf Gateway Deepwater Port at 28°02'16.20"N, 092°04'12.00"W is a floating storage and regasification unit. The first is a Safety Zone that has a 500 meter radius. The second is a mandatory No Anchoring Area that has a 1500 meter radius and the third is an Area to be Avoided that has a 2000 meter radius. The Safety Zone has been promulgated, via an Interim Rule published on May 11, 2005, Reference 68FR 25422-25425.

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

CAUTION
Gas and Oil Well Structures
Platforms, gas and oil well structures, some of which are submerged and capped, and submarine pipelines and cables are charted only where offshore of the indicated chart limits of the 1:80,000 scale series charts and Loop Deepwater Port chart 11359.

SOURCE

A	1990-2012	NOS Surveys	full bottom coverage
B3	1940-1969	NOS Surveys	partial bottom coverage
B4	1900-1939	NOS Surveys	partial bottom coverage
B5	Pre 1900	NOS Surveys	partial bottom coverage

SOURCE DIAGRAM
The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been bended in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Consult larger scale charts for survey information in areas outlined in magenta. Refer to Chapter 1, United States Coast Pilot.

MINERAL DEVELOPMENT STRUCTURES
Obstruction lights and sound (fog) signals are required for fixed mineral development structures shown on this chart, subject to approval by the District Commander, U.S. Coast Guard (33 CFR 67).

NOTE D
Regulations for Fixed Dumping Sites are contained in 40 CFR, Parts 220-229. Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (EPA), Region 6, Dallas, Texas, or from the nearest EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown.

NOTE C
CAUTION
Unexploded ordnance is known to exist in this area. Ordnance removed from the ocean floor should be reported to the U.S. Coast Guard the nearest EP disposal instructions.

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

NOTE G
The U.S. Coast Guard operates a mandatory Vessel Traffic Services (VTS) system in the Lower Mississippi River. Vessel operating procedures and designated radiotelephone frequencies are published in 33 CFR 161; the U.S. Coast Pilot; and/or the VTS User's Manual. Mariners should consult these sources for applicable rules and reporting requirements. Although mandatory VTS participation is limited to the navigable waters of the United States, certain vessels are encouraged or may be required, as a condition of port entry, to report beyond this area to facilitate advance vessel traffic management within the VTS area.

NOTE D
The hydrography with the heavy dashed black line was surveyed by NOS in 2005. A shoaling condition has been observed in relation to prior surveys. The density of this most recent survey data is inadequate to rule out the possibility of shoaler depths or undetected submerged features in these areas.



78th Ed., Aug 2014
11340

CAUTION
This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

HORIZONTAL DATUM
The horizontal reference datum of this chart is North American Datum 1983 (NAD 83) and for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 do not require conversion to NAD 83 for plotting on this chart.

NOAA encourages users to submit inquiries, discrepancies or comments about this chart at http://www.nauticalcharts.noaa.gov/staff/contact.htm.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

SOUNDINGS IN FATHOMS

FATHOMS	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
FEET	0	3	6	9	12	15	18	21	24	27	30	33	36	39	42	45	48	51	54
METERS	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18

Mississippi River to Galveston
SOUNDINGS IN FATHOMS - SCALE 1:458,596

11340

Last Correction: 8/31/2015. Cleared through:
LNM: 3315 (8/18/2015), NM: 3215 (8/8/2015)

To ensure that this chart was printed at the proper scale, the line below should measure six inches (152 millimeters).
If the line does not measure six inches (152 millimeters), this copy is not certified safe for navigation.

This chart was distributed as a PDF (Portable Document Format). Printing PDF's may alter the chart scale, color, or legibility that may impact suitability for navigation. Printed charts provided by NOAA-certified Print on Demand (POD) providers fulfill a vessel's requirement to carry a navigational chart "published by the National Ocean Service" in accordance with federal regulations including but not limited to 33 C.F.R. 164.33(a), 33 C.F.R. 164.72(b), and 46 C.F.R. 28.225(a). POD charts meet stringent print standards and can be recognized by an official certification of authenticity printed on the chart. A list of POD providers can be found at: nauticalcharts.noaa.gov/pod