Fairway LS 96, 1st Ed., Aug. 1906. KAPP 1915

JOINS CHART 14967

JOINS CHART 14965

SCALE 1:120,000
Nautical Miles
Statute Miles
Yards
Meters

Latitude and Longitude Plotting Interpolator

For more detail see Inset on Chart No.14967

For more detail see Chart No.14974

For more detail see Chart No.14973

For more detail see Chart No.14965

APOSTLE ISLANDS NATIONAL LAKESHORE
The Apostle Islands National Lakeshore boundary extends from the shoreline to 1 mile offshore.

MINNESOTA
WISCONSIN
SUPERIOR BAY
CHEQUAMEGON BAY
APOSTLE ISLANDS
KNIFE RIVER
DULUTH
SUPERIOR
BAYFIELD
WASHBURN
ASHLAND
CORNUCOPIA
PORT WING
TWO HARBORS
MINNESOTA

TWO HARBORS
MINNESOTA
Scale 1:10,000
SOUNDINGS IN FEET

PORT WING
WISCONSIN
Scale 1:5,000
SOUNDINGS IN FEET

CORNUCOPIA
WISCONSIN
Scale 1:5,000
SOUNDINGS IN FEET

KNIFE RIVER
MINNESOTA
Scale 1:5,000
SOUNDINGS IN FEET

SCALE 1:120,000
Nautical Miles
Statute Miles
Yards
Meters

NOAA
DEPARTMENT OF COMMERCE
COAST SURVEY

UNITED STATES - GREAT LAKES

LAKE SUPERIOR - MINNESOTA - WISCONSIN - MICHIGAN

LITTLE GIRLS POINT TO SILVER BAY

Polyconic Projection
Scale 1:120,000

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET

NOTES

PLANE OF REFERENCE OF THIS CHART (Low Water Datum).....601.1 ft.
Referred to mean water level at Rimouski, Quebec, International Great Lakes Datum (1985).

SAILING DIRECTIONS: Bearings of sailing courses are true and distances given thereon are in statute miles between points of departure.

AIDS TO NAVIGATION. Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

SYMBOLS AND ABBREVIATIONS. For complete list of symbols and abbreviations see Chart No. 1.

BRIDGE AND OVERHEAD CABLE CLEARANCES. When the water surface is above Low Water Datum, bridge and overhead clearances are reduced correspondingly. For clearances see U.S. Coast Pilot 6.

AUTHORITIES: Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey and U.S. Coast Guard.

Additional information can be obtained at nauticalcharts.noaa.gov.

Sailing courses and limits indicated in magenta are recommended by the Lake Carriers Association and the Canadian Shipowners Association.

NOTE B
The channel legend reflects the Corps of Engineers project depth. The Corps of Engineers publishes this controlling depth periodically in the U.S. Coast Guard Local Notice to Mariners. For further information on channel depths, direct inquiries to Office of the District Engineer, Corps of Engineers, Detroit, Michigan.

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

CAUTION
Due to periodic high water conditions in the Great Lakes, some features charted as visible at Low Water Datum may be submerged, particularly in the near shore areas. Mariners should proceed with caution.

MARINER ACTIVATED SOUND SIGNALS
Sound signals labeled with (WRASS) require user activation. See USCG Light List.

CAUTION
Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.
Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.
Station positions are shown thus:
⊙Accurate location) ⊙Approximate location)

Pump-out facilities

LAKE SUPERIOR
Duration in Years
Average levels (2003-2017)
Extreme Levels (period of record)

Low Water Datum, which is the plane of reference for the soundings on this chart, is the level that is as low as or lower than the elevation for the charted depths. If the lake level is above or below Low Water Datum, the existing depths are correspondingly greater or lesser than the charted depths.

HORIZONTAL DATUM
The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.05" southward and 0.80" westward to agree with this chart.

CAUTION
POTABLE WATER INTAKE
Vessels operating in fresh water lakes or rivers shall not discharge sewage, or ballast, or bilge water within such areas adjacent to domestic water intakes as are designated by the Commissioner of Food and Drugs 21 CFR 1250.93). Consult U.S. Coast Pilot 6 for important supplemental information.

NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 6. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 9th Coast Guard District in Cleveland, Ohio or at the Office of the District Engineer, Corps of Engineers in Detroit, Michigan.
Refer to charted regulation section numbers.

SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 6 for important supplemental information.

WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot 6 for details.

SOURCE

B2 1970-1989	NOS Surveys	partial bottom coverage
Pre-1974	Lake Survey Surveys	partial bottom coverage

SOURCE DIAGRAM
Most of the hydrography identified by the letter 'T' was surveyed by the U.S. Army Corps of Engineers prior to 1974. Other outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels currently maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

CAUTION
SUBMARINE PIPELINES AND CABLES
Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown.

Pipeline Area — Cable Area

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when navigating vessels with drafts or water compensators in their charts in areas where pipelines and cables may exist, and when anchoring, dragging, or fishing.
Covered wells may be marked by lighted or unlighted buoys.

NOTE Z
NO-DISCHARGE ZONE, 40 CFR 140
Michigan waters of Lakes Michigan, Huron, Superior, Erie and St. Clair; all waterways connected thereto; and all inland lakes are designated as a No-Discharge Zone (NDZ). Under the Clean Water Act, Section 312, all vessels operating within a No-Discharge Zone (NDZ) are completely prohibited from discharging any sewage, treated or untreated, whether from a holding tank or flow through macerator/disinfection system. All vessels with an installed marine sanitation device (MSD) that are navigating, moored, anchored, or docked within a NDZ must have the MSD disabled to prevent the overboard discharge of sewage (treated or untreated) or install a holding tank. Regulations for the NDZ are contained in the U.S. Coast Pilot. Information on pumpout facilities and the phase-in of these requirements may be obtained from the Environmental Protection Agency (EPA) web site: http://www.epa.gov/owow/oceans/regulatory/vessel_sewage/

NOAA WEATHER RADIO BROADCASTS
The NOAA Weather Radio station listed below provides continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be greater. Only 100 nautical miles for stations at high elevations.

Duluth, MN — KIG-64 — 162.550 MHz

CAUTION
Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.
During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.

SCALE 1:120,000
Nautical Miles
Statute Miles
Yards
Meters

| | | |