1st Ed., Jan. 1903 KAPP 1849

SOUNDINGS IN FEET

18656

TIDAL INFORMATION

PLACE		Height referred to datum of soundings (MLLW)		
NAME	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water
		feet	feet	feet
Suisun City	(38°14'N/122°02'W)	5.4	4.9	0.7
Antioch	(38°01'N/121°49'W)	3.9	3.4	0.6
Benicia	(38°03'N/122°08'W)	5.3	4.8	0.9
Crockett	(38°04'N/122°13'W)	5.9	5.4	1.0
Suisun Slough Entrance	(38°07'N/122°04'W)	4.7	4.2	0.7
Montezuma Slough Bridge	(38°11'N/122°59'W)	4.9	4.4	0.7

SUISUN BAY

TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO JUL 2015

NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH MLLW (FEET)
SUISUN PT. REACH	46	48	50	7-15	300	0.8	35
BULLS HEAD CHANNEL	37	34	35	7-15	300-350	1.2	35
EAST BULLS HEAD CHANNEL	34	35	33	7-15	350	1.1	35
PT. EDITH CROSSING RANGE	35	34	32	7-15	350	1.1	35
PRESTON PT. REACH	34	35	30	7-15	350	0.9	35
ROE ISLAND CHANNEL	34	35	34	7-15	350	1.1	35
PORT CHICAGO REACH	38	37	37	7-15	350	0.52	35
MIDDLE GROUND CHANNEL							
WEST REACH	36	37	36	7-15	350	1.29	35
EAST REACH	37	37	35	7-15	350	1.09	35
NEW YORK SLOUGH							
WEST REACH	33	34	35A	7-15	400	1.3	35
EAST REACH	33	35	32	7-15	400	1.7	35

(Column groups: CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW); PROJECT DIMENSIONS)

A. AN OBSTRUCTION WITH A DEPTH OF 36 FEET IS LOCATED AT 38°02'41.2" N 121°53'21.32" W

NOTE - CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

56th Ed., Aug. 2010

18656

CAUTION
This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

Last Correction: 10/7/2015. Cleared through:
LNM: 3815 (9/22/2015), NM: 4115 (10/10/2015)

To ensure that this chart was printed at the proper scale, the line below should measure six inches (152 millimeters).
If the line does not measure six inches (152 millimeters), this copy is not certified safe for navigation.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

This chart was distributed as a PDF (Portable Document Format). Printing PDFs may alter the chart scale, color, or legibility that may impact suitability for navigation. Printed charts provided by NOAA certified Print on Demand (POD) providers fulfill a vessel's requirement to carry a navigational chart "published by the National Ocean Service" in accordance with federal regulations, including but not limited to 33 C.F.R. 164.33(a), 33 C.F.R. 164.72(b), and 46 C.F.R. 28.225(a). POD charts meet stringent print standards and can be recognized by an official certification of authenticity printed on the chart. A list of POD providers can be found at: nauticalcharts.noaa.gov/pod

SOUNDINGS IN FEET

FATHOMS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
FEET	6	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102