Formerly C&GS 5575, 1st Ed., June 1945 D-1945-646. XAPP 1851

SOUNDINGS IN FEET



THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES - WEST COAST

CALIFORNIA

SUISUN BAY

ROE ISLAND AND VICINITY

Mercator Projection
Scale 1:10,000 at Lat 38° 04'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

For Symbols and Abbreviations see Chart No. 1

Additional information can be obtained at nauticalcharts.noaa.gov.

TIDAL INFORMATION

PLACE		Height referred to datum of soundings (MLLW)		
NAME	(LAT/LONG)	Mean Higher-High Water	Mean High Water	Mean Low Water
		feet	feet	feet
Port Chicago, Suisun Bay, California	(38°3.4' N/122°2.3' W)	4.8	4.4	0.7

Dashes (---) located in datum columns indicate unavailable datum values for a tide station. Real-time water levels, tide predictions, and total current predictions are available on the Internet from http://tidesandcurrents.noaa.gov.

(Aug 2001)

HEIGHTS

Heights in feet above Mean High Water.

SUISUN BAY

TABULATED FROM SURVEYS BY THE CORPS OF ENGINEERS - SURVEYS TO JUL 2015

CONTROLLING DEPTHS FROM SEAWARD IN FEET AT MEAN LOWER LOW WATER (MLLW)					PROJECT DIMENSIONS		
NAME OF CHANNEL	LEFT OUTSIDE QUARTER	MIDDLE HALF OF CHANNEL	RIGHT OUTSIDE QUARTER	DATE OF SURVEY	WIDTH (FEET)	LENGTH (NAUT. MILES)	DEPTH (FEET)
BULLS HEAD CHANNEL	37	34	35	7-15	300-500	1.2	35
EAST BULLS HEAD CHANNEL	34	35	33	7-15	350	1.1	35
FT. EDITH CROSSING RANGE	35	34	32	7-15	350	1.1	35
PRESTON PT. BEACH	34	35	30	7-15	350	0.9	35
ROE ISLAND CHANNEL	34	35	34	7-15	350	0.9	35
PORT CHICAGO REACH	36	37	37	7-15	350	0.52	35
MIDDLE GROUND CHANNEL							
WEST REACH	36	37	36	7-15	350	1.29	35
EAST REACH	37	37	35	7-15	350	1.09	35

NOTE : CONSULT THE CORPS OF ENGINEERS FOR CHANGES SUBSEQUENT TO THE ABOVE INFORMATION

CAUTION
SUBMARINE PIPELINES AND CABLES
Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Pipeline Area — Cable Area

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried; and those that were buried may now lie exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.
Covered weirs may be marked by lighted or unlighted buoys.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS-84). Positions obtained from charts of North American Datum of 1927 must be corrected an average of 0.286' southward and 3.849' westward to agree with this chart.

AIDS TO NAVIGATION

Consult U.S Coast Guard Light List for supplemental information concerning aids to navigation.

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

PLANE COORDINATE GRIDS

The California State Plane Coordinate Grid (Zone II) (based on NAD 1927) is indicated on this chart by dashed tick shown at 4000 foot intervals, thus: +
The last three digits are omitted.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers and U. S. Coast Guard.

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 7, Navigation Regulations, Chapter 7 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 11th Coast Guard District in Alameda, California or at the office of the District Engineer, Corps of Engineers in Sacramento, California.
Refer to charted regulation section numbers.

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Sacramento, CA	KEC-57	162.55 MHz WX1
Mt. Pisgo, CA	KHB-49	162.40 MHz WX2

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 7 for important supplemental information.

SOURCE DIAGRAM

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

SOURCE

A	2012	NOS Surveys	full bottom coverage
B2	1919-1989	NOS Surveys	partial bottom coverage

7462 X 1266.8 mm

31st Ed., Sep. 2007
18658

CAUTION
This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

Last Correction: 9/30/2015. Cleared through:
LNM: 3815 (9/22/2015), NM: 4015 (10/3/2015)

To ensure that this chart was printed at the proper scale, the line below should measure six inches (152 millimeters).
If the line does not measure six inches (152 millimeters), this copy is not certified safe for navigation.

NOAA encourages users to submit inquiries, discrepancies or comments about this chart at http://www.nauticalcharts.noaa.gov/staff/contact.htm.

SOUNDINGS IN FEET

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

This chart was distributed as a PDF (Portable Document Format). Printing PDFs may alter the chart scale, color, or legibility that may impact suitability for navigation. Printed charts provided by NOAA certified Print on Demand (POD) providers fulfill a vessel's requirement to carry a navigational chart "published by the National Ocean Service" in accordance with federal regulations, including but not limited to 33 C.F.R. 164.33(a), 33 C.F.R. 164.72(b), and 46 C.F.R. 28.225(a). POD charts meet stringent print standards and can be recognized by an official certification of authenticity printed on the chart. A list of POD providers can be found at: nauticalcharts.noaa.gov/pod

FATHOMS	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
FEET	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
METERS	0	0.5	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0

Suisun Bay, Roe Island and Vicinity
SOUNDINGS IN FEET - SCALE 1:10,000

18658