WEST INDIES

ST. THOMAS

SAINT THOMAS HARBOR

Mercator Projection
Scale 1:10,000 at Lat. 18°19'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

Additional information can be obtained at nauticalcharts.noaa.gov.

Formerly C&GS 933, 1st Ed., June 1917 V-1917-177 KAPP 285

AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

For Symbols and Abbreviations see Chart No. 1

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

TOTAL INFORMATION				
PLACE		Height referred to datum of soundings (MLLW)		
NAME	(LAT,LONG)	Mean Higher High Water	Mean High Water	Mean Low Water
		feet	feet	feet
Charlotte Amalie	(18°20'N,64°55'W)	0.8	0.7	0.1

Dashes (- -) located in datum columns indicate unavailable datum values for a tide station. Real-time water levels, tide predictions, and tidal current predictions are available on the Internet from http://tidesandcurrents.noaa.gov.

WARNING
The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

AUTHORITIES
Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the U.S. Coast Guard, Geological Survey, and National Geospatial-Intelligence Agency.

NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 5. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 7th Coast Guard District in Miami, Florida, or at the Office of the District Engineer, Corps of Engineers in Jacksonville, Florida.
Refer to charted regulation section numbers.

CORAL PROPAGATION
Uncharted submerged man-made structures, designed for the purpose of coral propagation, may exist within the limits of this chart, principally in shallow water areas.

LOGARITHMIC SPEED SCALE
1 2 3 4 5 6 7 8 9 10 15 20 25 30 40 50 60
To find SPEED, place one point of dividers on distance run (in any unit) and the other on minutes run. Without changing divider spread, place right point on 60 and left point will then indicate speed in units per hour. Example: with 4.0 nautical miles run in 15 minutes, the speed is 16.0 knots.

NOAA WEATHER RADIO BROADCASTS
The National Weather Service station listed below provides continuous weather broadcasts. The reception range is typically 20 to 40 miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

St. Thomas, V.I. WXM-96 162.475 MHz

HURRICANES AND TROPICAL STORMS
Hurricanes, tropical storms and other major storms may cause considerable damage to marine structures, aids to navigation and moored vessels, resulting in submerged debris in unknown locations.
Charted soundings, channel depths and shoreline may not reflect actual conditions following these storms. Fixed aids to navigation may have been destroyed or damaged, or may be lighted but not charted in their proper positions, damaged, sunk, extinguished or otherwise made inoperative. Mariners should not rely upon the position or operation of an aid to navigation. Wrecks and submerged obstructions may have been displaced from charted locations. Pipelines may have become uncovered or moved.
Mariners are urged to exercise extreme caution and are requested to report aids to navigation discrepancies and hazards to navigation to the nearest United States Coast Guard unit.

CAUTION
SUBMARINE PIPELINES AND CABLES
Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:
Pipeline Area — Cable Area
Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.
Covered weirs may be marked by lighted or unlighted buoys.

ANCHORAGE AREAS
110.250 (see note A)
Limits and designations of anchorage areas are shown in color.
(A) INNER HARBOR ANCHORAGE. (see note B)
(B) OUTER HARBOR ANCHORAGE-for vessels undergoing examination by Quarantine, Customs, Immigration, and Coast Guard Authorities. (see note B)
(D) GENERAL ANCHORAGE.
(C) (E) SMALL CRAFT ANCHORAGE.
(F) DEEP DRAFT ANCHORAGE.

NOTE B
Berths located in Anchorage Areas A and B are for requirements of the naval service, but all classes of vessels may anchor.

HEIGHTS
Heights in feet above Mean High Water.

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

CAUTION
Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.
Radio direction finder bearings to commercial broadcasting stations are subject to error and should be used with caution.
Station positions are shown thus:
⊙(Accurate location) ○(Approximate location)

SCALE 1:10,000
Nautical Miles 0 ½ 1
Yards 200 0 200 400 600 800 1000 1200
Meters 200 0 200 400 600 800 1000 1200

SOUNDINGS IN FEET

25649



SOUNDINGS IN FEET

25649

CAUTION
This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

This is the Last Edition of this chart. It will be canceled on Apr 3, 2024

20th Ed., Aug. 2010. Last Correction: 9/26/2023. Cleared through LNM: 1224 (9/19/2024). NM: 1324 (3/30/2024)

To ensure that the chart was printed at the proper scale, the line below should measure six inches (152 millimeters).
If the line does not measure six inches (152 millimeters), this copy is not certified safe for navigation.

This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

(POD) providers fulfill a vessel's requirement to carry a navigational chart "published by the National Ocean Service" in accordance with federal regulations, including but not limited to 33 C.F.R. 164.33(a), 33 C.F.R. 164.72(b), and 46 C.F.R. 28.225(a). POD charts meet stringent print standards and can be recognized by an official certification of authenticity printed on the chart. A list of POD providers can be found at: nauticalcharts.noaa.gov/pod

SOUNDINGS IN FEET

FATHOMS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
FEET	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
METERS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

Saint Thomas Harbor
SOUNDINGS IN FEET - SCALE 1:10,000

25649