SCALE 1:20,000
Nautical Miles
⅛ 0 ⅛ 1 1⅛
Yards
500 0 500 1000 1500 2000 2500
Meters
500 0 500 1000 1500 2000 2500

TIDAL INFORMATION

PLACE		Height referred to datum of soundings (MLLW)		
NAME	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water
		feet	feet	feet
Port Hueneme	(34°09'N/119°12'W)	5.4	4.7	1.0

Dashes (- -) located in datum columns indicate unavailable datum values for a tide station. Real-time water levels, tide predictions, and tidal current predictions are available on the Internet from: http://tidesandcurrents.noaa.gov.
(May 2013)

1st Ed., Mar. 2003 KAPP 1883

SOUNDINGS IN FATHOMS
(FATHOMS AND FEET TO 11 FATHOMS)

18724

CONTINUED ON CHART 18725

STACK (209ft) (Fl R 15s)

NOTE D
TRAFFIC SEPARATION SCHEME
One-way traffic lanes overprinted on this chart are RECOMMENDED for use by all vessels traveling between the points involved. They have been designed to aid in the prevention of collisions at the approaches to major harbors and along heavily traveled coastal waters, but are not intended in any way to supersede or to alter the applicable Rules of the Road. Separation zones are intended to separate inbound and outbound traffic and to be free of ship traffic. Separation zones should not be used except for crossing purposes. When crossing traffic lanes and separation zones use extreme caution.

NATIONAL MARINE SANCTUARIES
& MARINE PROTECTED AREAS
National Marine Sanctuaries are protected areas, administered by NOAA, which contain sensitive and diverse natural and cultural resources. These areas are particularly sensitive to environmental damage such as spills of oil and other hazardous materials, discharges and groundings. Exercise particular caution and follow applicable Sanctuary regulations when transiting these areas. A full description of Sanctuary regulations may be found in 15 CFR 922 and in the U.S. Coast Pilot. A full description of the federal regulations governing the Marine Protected Areas located within Channel Islands National Marine Sanctuary boundaries may be found in 15 CFR 922 and 50 CFR 660. A full description of the state regulations governing the Marine Protected Areas located within Channel Islands National Marine Sanctuary boundaries may be found in Title 14 California Code of Regulations (CCR) section 632.

CAUTION
Submarine Pipelines
Uncharted submarine pipelines may exist in the vicinity of oil well structures, and between such structures and the shoreline. Mariners should use caution when anchoring.

SOURCE DIAGRAM
The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot.

SOURCE

A	1990-2001	NOS Surveys	full bottom coverage
B1	1990-2005	NOS Surveys	partial bottom coverage
B2	1970-1989	NOS Surveys	partial bottom coverage
B4	1900-1939	NOS Surveys	partial bottom coverage
B5	1834-1899	NOS Surveys	partial bottom coverage

NOTE S
Regulations for Ocean Dumping Sites are contained in 40 CFR, Parts 220-228. Additional information concerning the regulations and requirements for use of the sites may be obtained from the Environmental Protection Agency (EPA). See U.S. Coast Pilots appendix for addresses of EPA offices. Dumping subsequent to the survey dates may have reduced the depths shown.

NOTE C
CAUTION
Area subject to rapid shoaling. Depths from survey of 2017.

Ⓟ Pump-out facilities

SUPPLEMENTAL INFORMATION
Consult U.S. Coast Pilot 7 for important supplemental information.

NOTE Z
NO-DISCHARGE ZONE, 40 CFR 140
Under the Clean Water Act, Section 312, all vessels operating within a No-Discharge Zone (NDZ) are completely prohibited from discharging any sewage, treated or untreated, into the waters. All vessels with an installed marine sanitation device (MSD) that are navigating, moored, anchored, or docked within a NDZ must have the MSD disabled to prevent the overboard discharge of sewage (treated or untreated) or install a holding tank. Regulations for the NDZ are contained in the U.S. Coast Pilot. Additional information concerning the regulations and requirements may be obtained from the Environmental Protection Agency (EPA) web site: http://www.epa.gov/owow/oceans/regulatory/vessel_sewage/.

THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES - WEST COAST

CALIFORNIA

PORT HUENEME AND APPROACHES

Mercator Projection
Scale 1:20,000 at Lat. 34° 08'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FATHOMS
(FATHOMS AND FEET TO ELEVEN FATHOMS)
AT MEAN LOWER LOW WATER

For Symbols and Abbreviations see Chart No. 1

COLREGS: International Regulations for Preventing Collisions at Sea, 1972.
Demarcation lines are shown thus: — — — —

Additional information can be obtained at nauticalcharts.noaa.gov.

HEIGHTS
Heights in feet above Mean High Water.

AUTHORITIES
Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

POLLUTION REPORTS
Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

RADAR REFLECTORS
Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

NOTE A
Navigation regulations are published in Chapter 2, U.S. Coast Pilot 7. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at: the Office of the Commander, 11th Coast Guard District in Alameda, California or at the Office of the District Engineer, Corps of Engineers in Los Angeles, California.
Refer to charted regulation section numbers.

MINERAL DEVELOPMENT STRUCTURES
Obstruction lights and sound (fog) signals are required for fixed mineral development structures shown on this chart, subject to approval by the District Commander, U.S. Coast Guard (33 CFR 67).

NOAA WEATHER RADIO BROADCASTS
The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

Santa Barbara, CA	KIH-34	162.400 MHz
Santa Barbara Marine, CA	WWF-62	162.475 MHz

CAUTION
Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.
Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.
Station positions are shown thus:
⊙(Accurate location) o(Approximate location)

HORIZONTAL DATUM
The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.019" northward and 3.390" westward to agree with this chart.

CAUTION
Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

CAUTION
Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

AIDS TO NAVIGATION
Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

CAUTION
SUBMARINE PIPELINES AND CABLES
Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.
Covered wells may be marked by lighted or unlighted buoys.

PORT HUENEME
Scale 1:12,500
SCALE 1:12,500 KAPP 1882
Yards 100 0 100 200 300 400 500 600
Iso R 6s 87ft
Q R 63ft
(STORM WARNING)
RESTRICTED AREA 334.1127 (see note A)
Fl (5) 30s 52ft 14M HORN (MRASS see note K)
COLREGS DEMARCATION LINE 80.1120 (see note A)
Disposal Area Depths from survey of 2015-2017
SAFETY FAIRWAY 166.300 (see note A)
Current Meter (top bpx 9 fms 3 ft)

Channel Islands Harbor

NOTE K
MARINER ACTIVATED SOUND SIGNALS
Sound signals labeled with (MRASS) require user activation. See USCG Light List.

IMO AMENDED TRAFFIC SEPARATION SCHEME
Portions of the traffic separation scheme shown on this chart have been amended by the IMO. See IMO COLREG.2/Circ.64 and COLREG.2/Circ.79 Annex 2.
Please be advised that these portions have not been revised by the United States Coast Guard and that the corresponding changes have not been updated in the Code of Federal Regulations (33 CFR part 167). There are differences between the two traffic separation schemes and caution is advised.

NO-DISCHARGE ZONE (see note Z)

PORT HUENEME

Iso R 6s 87ft
Q R 63ft
Pt Hueneme (see inset)
TANKS
Fl (5) 30s 52ft 14M HORN (MRASS see note K)
RESTRICTED AREA 334.1127 (see note A)
Fl R 2.5s 31ft 5M "4"
Fl G 2.5s 42ft 5M "3"
COLREGS DEMARCATION LINE 80.1120 (see note A)
Disposal Area Depths from surveys of 2015-2017
RW "PH" Mo(A) WHIS
Current Meter (top bpx 9 fms 3 ft)
Pier
Dunes
Ormond Beach
STACKS (F R Lts)
TOWERS
RESTRICTED AREA 334.1126 (see note A)

Oxnard Shores

Fl G 4s 30ft 5M "5"
Fl 4s 35ft 5M
Fl G 4s 36ft 5M "3"
Fl R 4s 39ft 5M "4"
Fl R 2.5s 30ft 5M "2" HORN (MRASS see note K)
Fl G 6s 54ft 5M "1"
COLREGS DEMARCATION LINE 80.1122 (see note A)
COLREGS DEMARCATION LINE 80.1122 (see note A)
NAUTICAL MILE COURSE 327° 51' TRUE
THREE NAUTICAL MILE LINE (see note N)
Fl G 2.5s 42ft 5M "3"
Fl R 2.5s 31ft 5M "4"
RESTRICTED AREA 334.1127 (see note A)
Disposal Area Depths from survey of 2015-2017
COLREGS DEMARCATION LINE 80.1120 (see note A)
SAFETY FAIRWAY 166.300 (see note A)
Current Meter (top bpx 9 fms 3 ft)
Pilots
Obstn
Fish Haven
Wreckage
"GINA"
SAFETY ZONE 147.1103 (see note A)
SANTA BARBARA CHANNEL
Hueneme Canyon
CHANNEL ISLANDS NATIONAL MARINE SANCTUARY (protected area: 15 CFR 922; see note A and National Marine Sanctuaries note)
NORTH-WESTBOUND TRAFFIC LANE
SOUTH-EASTBOUND TRAFFIC LANE
SEPARATION ZONE (see note D)
Dump Site (discontinued) (dredged material) (see note S) Depths from survey of 1977
AREA TO BE AVOIDED (see note E)
THREE NAUTICAL MILE LINE (see note N)
CAUTION PT MUGU SEA RANGE
Cable Area

NOTE E
AREA TO BE AVOIDED
All ships, except those bound to and from ports on one of the islands within the area, engaged in the trade of carrying cargo, including but not limited to tankers and other bulk carriers and barges, should avoid the areas (MSC, IMO 59/33 Annex 21; IMO SN.1/Circ.347 Annex 2).

NOTE X
Within the 12-nautical mile Territorial Sea, established by Presidential Proclamation, some Federal laws apply. The Three Nautical Mile Line, previously identified as the outer limit of the territorial sea, is retained as it continues to depict the jurisdictional limit of the other laws. The 9-nautical mile Natural Resource Boundary off the Gulf coast of Florida, Texas, and Puerto Rico, and the Three Nautical Mile Line elsewhere remain in most cases the inner limit of Federal fisheries jurisdiction and the outer limit of the jurisdiction of the states. The 24-nautical mile Contiguous Zone and the 200-nautical mile Exclusive Economic Zone were established by Presidential Proclamation. Unless fixed by treaty or the U.S. Supreme Court, these maritime limits are subject to modification.

MAGNETIC
VAR 12° 45' E (2013)
ANNUAL DECREASE 6'
Fl (5) Y 20s Priv
S "W" Priv
R "N "OB2" Priv

CONTINUED ON CHART 18740

CONTINUED ON CHART 18725

CAUTION
This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov.

NOAA encourages users to submit inquiries, discrepancies or comments about this chart at http://www.nauticalcharts.noaa.gov/staff/contact.htm.

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

SOUNDINGS IN FATHOMS
(FATHOMS AND FEET TO 11 FATHOMS)

FATHOMS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17
FEET 6 12 18 24 30 36 42 48 54 60 66 72 78 84 90 96 102
METERS 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

Port Hueneme
SOUNDINGS IN FATHOMS - SCALE 1:20,000

18724

This is the Last Edition of this chart. It will be canceled on Jul 31, 2024

3rd Ed., Jun. 2013. Last Correction: 1/29/2024. Cleared through:
LNM: 1624 (4/16/2024), NM: 1724 (4/27/2024)

To ensure that this chart was printed at the proper scale, the line below should measure six inches (152 millimeters).
If the line does not measure six inches (152 millimeters), this copy is not certified safe for navigation.

(POD) providers fulfill a vessel's requirement to carry a navigational chart "published by the National Ocean Service" in accordance with federal regulations, including but not limited to 33 C.F.R. 164.33(a), 33 C.F.R. 164.72(b), and 46 C.F.R. 28.225(a). POD charts meet stringent print standards and can be recognized by an official certification of authenticity printed on the chart. A list of POD providers can be found at: nauticalcharts.noaa.gov/pod

Reproduction of this chart may be restricted by law. Unauthorized reproduction may subject violators to criminal, civil, or administrative proceedings. Not to be used for navigation.